

Device under test

| Device under lest | | |
|-----------------------|--------------------------------------|-------------------------|
| Manufacturer | | Christie |
| Model | | Boxer 4k30 |
| Firmware | | Boxer 1.0.2 |
| Capabilities over TPS | Native panel resolution | 4096x2160 |
| | Light processing | 3-chip DLP |
| | EDID 1 st detailed timing | 2048x1080@60 |
| | EDID 2 nd detailed timing | 1920x1080@60 |
| | HDMI capable | ✓ |
| | HDCP capable | ✓ |
| | Supported color depths | 24/30/36 bits per pixel |
| | Audio support | × |
| | IR support | \checkmark |
| | RS232 support | × |
| | Ethernet support | ✓ |
| | Longreach support | ✓ |

| Measurement results | | | |
|-----------------------------|-------------------|---|--|
| TPS HDBaseT video support | MX-TPS-OB | PASS | |
| | UMX-TPS-TX140 | | |
| | DVI-HDCP-TPS-TX95 | 3840x2160 30 Hz 36 bpp up to 100 m with CAT5e | |
| | HDMI-TPS-TX95 | | |
| TPS Longreach video support | MX-TPS-OB | PASS 1920x1080 60 Hz 24 bpp up to 170 m with CAT7 S/FTP AWG23 | |
| | UMX-TPS-TX140 | | |
| | DVI-HDCP-TPS-TX95 | | |
| | HDMI-TPS-TX95 | | |
| TPS audio support | | N/A | |
| TPS HDCP support | | PASS | |
| TPS ethernet support | | PASS | |
| TPS serial support | | N/A | |
| TPS IR support | | PASS | |

Overall verdict

Lightware compatibility

All tests passed which supported by the DUT. The tested device is compatible with all Lightware TPS devices.

HDBaseT[™] and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance

